

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **06188926 A**

(43) Date of publication of application: 08 . 07 . 94

(51) Int. Cl.

H04L 27/18**H04L 27/20****H04L 27/22**(21) Application number: **04356248**(22) Date of filing: **21 . 12 . 92**

Kuwa Patent Attorneys
Osaka

(71) Applicant: **TOYO COMMUN EQUIP CO LTD**

(72) Inventor:
YANAGISAWA SHIGEKI
MATSUO KAZUTO
WADA YOSHIO
MORIZUMI TETSUYA

(54) **METHOD FOR PSK MODULATION AND
 DEMODULATION AND DEVICE THEREFOR**

demodulate original information data $D(t)$, thus
 improving the error rate.

(57) Abstract:

COPYRIGHT: (C)1994,JPO&Japio

PURPOSE: To provide the method for PSK modulation/demodulation and device therefor which reduce the error rate for demodulation of a PSK modulation signal in comparison with a delay detecting means and a synchronous demodulating means.

CONSTITUTION: A modulator T sends the signal obtained by noninverting or inverting the carrier wave, whose instantaneous value starts with a prescribed value, in accordance with each bit value of information data $D(t)$ as a PSK modulation signal $P(t)$ from a terminal (e) of a switch circuit 6. Meanwhile, a demodulator R uses a wavelet converter 10 and obtains a value $W(a, b)$, which is obtained by subjecting the PSK modulation signal $P(t)$ to wavelet conversion by a function $h_{a,b}(t)$ for emphasis of only the phase change component of the PSK modulation signal $P(t)$, to eliminate the noise included in the signal component other than the phase change component of the PSK modulation signal $P(t)$. Simultaneously, a bit value corresponding to the polarity of the converted value $W(a, b)$ is outputted from a polarity discriminator 13 to

